

Product Description

- Cut 2, 15 gauge Polyester outer liner with a 7 gauge Acrylic-loop Thermal inner liner
- Fully coated in Smooth Latex, finished with a Sandy Latex palm dip
- Suitable for use inside or outside, in wet or dry; cold or warm conditions
- Superb wet or dry grip
- Extremely comfortable and dexterous
- Elasticated cuff with coloured cuff size indicator
- Contact Cold Level 2

Specifications

Code: WS4	Size Range: 8 to 11
Liner: Polyester/ Acrylic	Pack Size: 10 pairs
Gauge: 15/7	Case Size: 120 pairs
Coating: Sandy Latex	EN388: 2242X
	EN511: X21

Suggested Applications

- Construction
- Scaffolding
- Infrastructure
- Banksmen
- Engineering
- Landscaping
- Cold Stores and Refrigeration

Certification and Marking



Limitations of Use

Maintenance	Examine gloves for damages, splits and holes before each use. Always replace damaged gloves. Only properly fitting gloves guarantee protection and grip.
Storage	Store at normal room temperature in a dry, well ventilated area. Avoid direct heat radiation.
Disposal	Used gloves can be contaminated. Dispose with household waste or as instructed by your local authority.
Cleaning	Do not wash. The performance of the product after laundering is unknown. Beat or brush out after each use, depending on level of dirt.
Durability	The period of use depends on the degree or intensity of use in the retrospective application. It is therefore not possible to provide a 'life span' of the gloves.
Note	Due to the nature of this product the user is advised to carry out their own risk assesment before use, depending on application.
Warning	This product contains natural rubber latex which could cause anaphylactic responses.